

IN THE CLAIMS

Please amend claims 1 and 19 to read as follows. The amendments are shown in Appendix A.

1. A pre-fabricated wall panel usable with a door or window jamb without jamb furring, comprising:
 - a first, exterior facing sheet of generally rigid material and having a first thickness and a first sheet perimeter;
 - a second, interior facing sheet of generally rigid material and having a second thickness and a second sheet perimeter, said second sheet being generally parallel to said first sheet and spaced therefrom a strut thickness;
 - at least two framing struts being located between said first sheet and said second sheet and having said strut thickness to define a panel volume between said first sheet, said second sheet, and said framing struts;
 - a polymeric in-situ foam core located in and substantially filling said panel volume; and,
 - an overall panel thickness including the sum of said first thickness, said second thickness and said strut thickness, said overall panel thickness being four inches, plus/minus ¼ inch.

19. A building assembly, comprising:
 - at least two pre-fabricated wall panels usable with a door or window jamb without jamb furring connected to each other, each of said wall panels including
 - a first, exterior facing sheet of generally rigid material and having a first thickness and a first sheet perimeter;
 - a second, interior facing sheet of generally rigid material and having a second thickness and a second sheet perimeter, said second sheet being generally parallel to said first sheet and spaced therefrom a strut thickness;

at least two framing struts being located between said first sheet and said second sheet and having said strut thickness to define a panel volume between said first sheet, said second sheet, and said framing struts;

a polymeric in-situ foam core located in and substantially filling said panel volume; and,

an overall panel thickness including the sum of said first thickness, said second thickness and said strut thickness, said overall panel thickness being four inches, plus/minus $\frac{1}{4}$ inch;

a jamb member secured adjacent at least one of said struts; and,

sheets of drywall secured adjacent said second panels, said drywall having an interior surface that is flush with a jamb member interior edge.